



Aluminium Sulphate

AS-17

CAS No.: 10043-01-3

Formula: $\text{Al}_2(\text{SO}_4)_3$

DESCRIPTION

Aluminium Sulphate is a white granular or powdered coagulant widely used in water and wastewater treatment, paper production, and various industrial processes. It works by neutralising charges on suspended solids, promoting floc formation, and enabling efficient clarification and separation of impurities.

KEY FEATURES

- High-purity alumina content ($\geq 17\%$) ensuring strong coagulation efficiency
- Low iron content for colour-critical applications
- Excellent solubility and controlled particle size distribution
- Effective pH adjustment and charge-neutralisation capacity
- Suitable for potable water, industrial, and paper manufacturing uses

APPLICATIONS

- Water and wastewater treatment (coagulant / flocculant)
 - Paper manufacturing (sizing and retention aid)
 - Dyeing and printing auxiliaries
 - Leather tanning and hide preparation
 - Construction additives and specialty formulations
-



LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

TYPICAL SPECIFICATIONS

Parameter	Specification
Appearance	Granule or powder
Colour	White
Odour	Weak
pH (1 % solution)	3.5
Al ₂ O ₃ content	≥ 17.00 %
Fe ₂ O ₃ content	≤ 0.003 %
Water Insoluble Matter	≤ 0.10 %
Arsenic (As)	≤ 14 mg/kg Al
Cadmium (Cd)	≤ 3 mg/kg Al
Chromium (Cr)	≤ 30 mg/kg Al
Mercury (Hg)	≤ 4 mg/kg Al
Nickel (Ni)	≤ 20 mg/kg Al
Lead (Pb)	≤ 40 mg/kg Al
Antimony (Sb)	≤ 20 mg/kg Al
Selenium (Se)	≤ 20 mg/kg Al

PARTICLE SIZE AVAILABILITY

Standard particle sizes (selected to customer requirements):

- 1 mm
- 2 mm
- 2.5 mm

More than 90 % of product meets the specified size range.

PACKAGING

- 25 kg, 50 kg, 1000 kg, and 1250 kg bags
- Palletised and shrink-wrapped
- Custom packaging available upon request.

STORAGE

Store in a cool, dry, well-ventilated area.

Keep container tightly sealed to prevent moisture absorption.

Avoid contact with bases, chlorates, chlorites, strong oxidising agents, and foodstuffs.

SAFETY & HANDLING

Use with adequate ventilation and personal protective equipment.

Avoid inhalation of dust and contact with eyes or skin.

Refer to the product Safety Data Sheet (SDS) for full safety and first-aid details.