



METHOD™ HEMC 20K

Methyl Hydroxy Ethyl Cellulose

CAS Number: 9032-42-2

DESCRIPTION

METHOD™ HEMC 20K is a non-ionic methyl hydroxy ethyl cellulose ether designed for use in tile adhesives, cement-based plasters, renders, skim coats, and drymix construction systems. The product provides excellent water retention, workability, open time, and heat stability while improving adhesion and application performance in cementitious formulations.

KEY FEATURES

- Excellent water retention
- Improves workability and trowelling properties
- Extended open time
- Good heat stability
- Enhances adhesion
- Suitable for drymix mortar systems

APPLICATIONS

- Excellent water retention
- Improves workability and trowelling properties
- Extended open time
- Good heat stability
- Enhances adhesion
- Suitable for drymix mortar systems

TYPICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Appearance	White Powder
Viscosity (2% Solution, 20°C, Brookfield, 20 rpm)	18,000 – 25,000 mPa·s
pH	5.0 – 9.0
Particle Size (through 80 mesh)	≥95%
Moisture Content	≤6.0%



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

Available in 25 kg paper bags with polyethylene inner liner.

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated environment away from direct sunlight and moisture. Shelf life is 24 months when stored in unopened original packaging under recommended conditions.

SAFETY

Refer to the Safety Data Sheet (SDS) for detailed safety, handling, transport, and regulatory information.