



CS-202

Methyl Hydrogen Silicone Fluid

CAS # 63148-57-2

CS-202 is a reactive methyl hydrogen silicone fluid that is colorless, tasteless, and transparent. It contains active Si-H groups capable of forming crosslinked films in the presence of suitable catalysts, enabling outstanding water repellency and surface protection. When applied to porous and mineral-based substrates, CS-202 creates a breathable hydrophobic barrier that allows moisture vapor to escape while preventing liquid water penetration. It is used across multiple industries including construction materials, paper processing, and specialty coatings.

BENEFITS & FEATURES

- Strong hydrophobic performance on porous substrates
- Breathable film formation allows moisture vapor release
- Improves resistance to mold, efflorescence, and water damage
- Low application dosage with efficient performance
- Compatible with both acidic and alkaline mineral surfaces

USAGE GUIDELINES

CS-202 is suitable for direct addition into wet formulations or for post-treatment of finished materials, depending on the end use. For slurry-based systems such as gypsum or cement, it is recommended to disperse evenly during mixing. For surface applications, it may be diluted and applied via spraying or brushing, followed by curing with metal salt catalysts. Typical usage levels range from 0.1% to 0.5% by weight of dry binder or substrate, though field trials should be conducted to optimize performance for specific applications.

SPECIFICATIONS

Parameters	Specification
Appearance	Colorless, tasteless liquid
Viscosity (25°C, mm ² /s)	17 – 25
Specific Gravity	0.995 – 1.015
Hydrogen Content (%)	≥ 1.55
pH (10% in water)	5.0 – 7.0





LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia

chemport.com.au

PACKAGING

Available in 200 kg drums and 1000 kg IBC totes

STORAGE

Store in tightly sealed containers in a cool, ventilated, and dry environment. Keep away from direct sunlight, high heat, and sources of ignition. Avoid contamination with acids, alkalis, oxidizing agents, and moisture. Proper storage ensures a shelf life of 12 months.

SAFETY

Avoid direct contact with skin and eyes. Use appropriate personal protective equipment. Do not ingest or inhale vapors. Refer to the Safety Data Sheet (SDS) for detailed guidance on safe handling, first aid, and disposal procedures.