



EDTMP•Na5

Pentasodium Salt of Ethylene Diamine Tetra (Methylene Phosphonic Acid)

CAS # 7651-99-2

EDTMP•Na5 is a high-purity aqueous solution of the pentasodium salt of ethylenediamine tetra(methylene phosphonic acid). It is a nitrogen-containing organophosphonic acid derivative used extensively as a chelating agent and scale inhibitor. The product exhibits excellent thermal stability and corrosion inhibition, particularly in high-temperature industrial water treatment applications. It is highly effective against calcium and barium sulfate scaling and forms stable complexes with multiple metal ions, enhancing system cleanliness and operational efficiency.

KEY FEATURES

- Strong chelating performance with multivalent metal ions
- Effective scale inhibition for calcium and barium sulfates
- Excellent thermal and chemical stability up to 200°C
- Nitrogenous phosphonate structure provides cathodic corrosion inhibition
- Fully water-soluble and environmentally friendly profile

USAGE GUIDELINES

EDTMP•Na5 is recommended for use in industrial water treatment systems, boiler feedwater, cooling towers, and other applications where scale and corrosion control is essential. It may also be used in dyeing, electroplating, and detergent formulations.

Typical dosage rates should be determined through pilot testing based on system composition, temperature, and operating conditions.

SPECIFICATIONS

Items	Index
Appearance	Amber transparent liquid
Active content (as EDTMPA) %	24.0–26.0
Active content (as EDTMP•Na ₅) %	30.0–32.6
Chloride (Cl ⁻) %	2.0 max
Density (20°C) g/cm ³	1.25 min
Fe, mg/L	20.0 max
pH (as it)	6.0–8.0





LIMITED WARRANTY INFORMATION. PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia



chemport.com.au

PACKAGING

Available in 200L plastic drums, 1000L IBCs, or customized packaging upon request.

STORAGE

- Store in tightly sealed containers in a cool, dry, well-ventilated area
- Protect from direct sunlight and freezing conditions
- Shelf Life: 10 months from date of manufacture under recommended storage conditions

SAFETY

Refer to the current Safety Data Sheet (SDS) before handling. Ensure appropriate PPE and ventilation are used when handling the product.