



Powder Defoamer SL-01

DESCRIPTION

Powder Defoamer SL-01 is a free-flowing powdered defoamer specifically developed for self-levelling compounds, cementitious systems, and drymix formulations. Manufactured using active polyether and organosilicon technologies absorbed onto mineral carriers, the product delivers rapid foam elimination and long-lasting anti-foaming performance. It reduces entrained air, improves density, and enhances surface finish in cement-based systems.

KEY FEATURES

- Rapid defoaming performance
- Long-lasting anti-foaming effect
- Reduces entrained air content
- Improves density and surface quality
- Excellent compatibility with mortar additives
- Suitable for alkaline drymix systems
- Easy incorporation into dry blends

APPLICATIONS

- Self-levelling compounds
- Repair mortars
- Rendering mortars
- Cement-based systems
- Gypsum-based systems
- Drymix construction materials

TYPICAL SPECIFICATIONS

Appearance	White Powder
Active Content, %	30 – 60
Bulk Density, g/L	300 – 600
Moisture Content, %	≤ 5.0
Defoaming Time	≤ 60 seconds
Anti-Foaming Duration	≥ 2 hours



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

Available in 20 kg bags and customised packaging options upon request.

STORAGE & HANDLING

Store in a cool, dry environment away from moisture and direct sunlight. Keep containers tightly sealed when not in use. Avoid exposure to conditions that may result in caking or product degradation.

SAFETY

Avoid inhalation of dust and contact with eyes or skin. Use appropriate PPE including gloves, safety glasses, and dust masks. Refer to the Safety Data Sheet (SDS) for detailed safety and handling information.