



Powder Defoamer-018

DESCRIPTION

Powder Defoamer-018 is a high-performance non-silicone powdered defoaming additive developed for drymix mortars, cementitious systems and powder coating applications. It provides rapid foam elimination and long-lasting foam control, helping improve density, surface finish and overall formulation performance.

KEY FEATURES

- Non-silicone defoamer technology
- Rapid foam elimination
- Long-lasting foam suppression
- Phosphorus-free formulation
- Easy incorporation into dry powder blends
- Suitable for cementitious systems
- REACH SVHC compliant composition

APPLICATIONS

- Drymix Mortars
 - Tile Adhesives
 - Cementitious Grouts
 - Self-Levelling Compounds
 - Renders & Plasters
 - Powder Coatings
-

TYPICAL SPECIFICATIONS

Property	Specification
Appearance	White to Off-White Powder
pH	5.0 – 7.0
Form	Free Flowing Powder



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

RECOMMENDED DOSAGE

Typical addition levels range from 0.05% to 0.30% by weight of total formulation. Optimum dosage should be determined through laboratory and production trials.

METHOD OF USE

Powder Defoamer-018 may be incorporated directly into dry powder formulations during blending or added as a component within formulated drymix systems. Optimum addition point and dosage should be determined through application testing.

PACKAGING

Available in 15 kg bags. Alternative packaging options may be available upon request.

STORAGE & HANDLING

Store in original unopened packaging in a cool, dry location away from direct sunlight and sources of heat.

Shelf Life: 12 months from date of manufacture when stored under recommended conditions.

SAFETY

Avoid inhalation of dust and direct contact with skin or eyes. Use appropriate personal protective equipment and follow good industrial hygiene practices. Refer to the Safety Data Sheet (SDS) for detailed information regarding safe handling, storage and disposal.