



Polyvinyl Alcohol (PVA) 05-88

CAS No.: 9002-89-5

Formula: $(C_2H_4O)_n$

DESCRIPTION

Polyvinyl Alcohol 05-88 is a partially hydrolysed, water soluble polymer used as a binder, film former and protective colloid. Its balance of viscosity and solubility makes it suitable for adhesives, construction materials, ceramics, textile sizing, emulsions and a wide range of industrial formulations.

KEY FEATURES

- Excellent film-forming properties
- Strong adhesion and cohesive strength
- Good emulsification and suspension stability
- Low ash content
- Consistent viscosity and performance
- Good compatibility with inorganic fillers and pigments

APPLICATIONS

- Construction admixtures, cement modifiers and redispersible polymer systems
- Adhesives and glues
- Ceramic binder formulations
- Emulsion polymerisation
- Textile warp sizing
- Paper and packaging coatings
- Water-soluble films

TYPICAL SPECIFICATIONS

Parameter	Specification
Hydrolysis (Mol percent)	86.0 to 90.0
Viscosity (4% solution, mPa·s)	4.0 to 7.0
Volatile Matter (%)	≤ 7.0
Ash (%)	≤ 0.7
pH (4% solution)	5 to 7
Purity (%)	≥ 91.5



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

- 25 kg bags
- 500 kg bulk bags
- 1000 kg bulk bags (subject to availability)

STORAGE

Store in a dry, cool environment away from moisture. Keep bags tightly sealed when not in use. Avoid exposure to humidity to prevent lumping and loss of flowability.

SAFETY & HANDLING

Avoid breathing dust. Use appropriate PPE including dust mask, goggles and gloves. Handle in well ventilated areas. Refer to the Safety Data Sheet for full details.