



Calcium Lignosulfonate

CAS No.: 8061-52-7
Formula: $C_{20}H_{24}CaO_{10}S_2$

DESCRIPTION

Calcium Lignosulfonate is a light yellow to brown powder derived from the sulfite pulping of softwood. It is soluble in water but practically insoluble in organic solvents. Its dispersing, binding, and chelating properties make it a versatile additive across construction, agriculture, and industrial sectors.

KEY FEATURES

- Renewable, lignin-derived additive
- Excellent dispersant and water reducer
- Functions as a binder, chelating agent, and plasticizer
- Suitable for multiple industries including construction, agriculture, and leather tanning

APPLICATIONS

- Concrete admixtures (plasticizer/water reducer)
- Oil well cementing
- Leather tanning
- Dyestuffs and pigments
- Chelating agent in horticulture
- Binder in animal feeds

TYPICAL SPECIFICATIONS

Parameter	Specification
Appearance	Light brown powder
Moisture (%)	≤ 6.0
pH	6 – 8
Lignosulfonate (%)	≥ 55
Reducing Sugar (%)	≤ 8.0
Sulfate as SO_4 (%)	2 – 5
Water Insoluble Matter (%)	≤ 2
Solids Content (%)	≥ 93



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

- 25 kg bags
- Super sacks

STORAGE

Store in a dry place away from direct sunlight. Keep in sealed, original packaging to maintain product integrity.

SAFETY & HANDLING

Refer to the Safety Data Sheet (SDS) for detailed information on safe handling, personal protective equipment, first aid measures, and disposal considerations.