



Sodium Lignosulfonate Solution 40%

CAS No.: 8061-51-6

Formula:

DESCRIPTION

Sodium Lignosulfonate Solution 40% is a brown liquid derived from the sulfite pulping of wood. It is a natural, water-soluble anionic polymer with dispersing, complexing, and surface-active properties. The product functions as a low-range water reducer in concrete and as a mid-temperature retarder in oil-well cementing systems. Its multifunctional chemistry makes it suitable for use across diverse industrial applications requiring dispersion, binding, or stabilization.

KEY FEATURES

- Organic, environmentally friendly dispersant
- Effective mid-temperature retarder for oilfield cementing
- Enhances water reduction and workability in concrete systems
- Compatible with most cement additives and admixtures
- Also used as a binder, emulsifier, or dispersant in agrochemical and industrial formulations

APPLICATIONS

- Concrete admixtures (water reducer, plasticizer)
- Oilfield cementing retarder
- Pellet binding and briquetting
- Agrochemicals, pesticides, and fertilizer formulations
- Textile and dyestuff dispersant systems

TYPICAL SPECIFICATIONS

Parameter	Specification
Appearance	Brown liquid
Solids Content	≥ 40.0%
pH (25 °C)	9.5 – 10.5
Specific Gravity	1.23 – 1.25 g/mL



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

- Available in 1,000 L IBC totes and bulk tankers.
- Other packaging options may be available upon request.

SHELF LIFE

Shelf life is at least 12 months under normal storage conditions.

STORAGE

Store in sealed original containers in a dry, well-ventilated area away from direct sunlight and frost.
Avoid prolonged exposure to high temperature or contamination.

SAFETY & HANDLING

Avoid contact with eyes and skin. Use suitable protective equipment including gloves and goggles during handling.
Do not ingest or inhale mist. In case of contact, rinse thoroughly with water.
Refer to the Safety Data Sheet (SDS) for detailed first-aid, handling, and disposal information.