



DEFOAMER AG200

Defoamer AG200 is a liquid defoaming agent used in concrete admixture and cement-based products. It is easily dispersed in water and with other concrete admixtures. When mixed with concrete, AG200 prevents excess air entrainment which is caused by general foam and regenerating air, and it also maintains an even amount of air in the concrete. Defoamer AG200 is also stable during the transportation of readymix concrete.

USAGE

The recommended dosage rate in concrete admixture is 0.05-0.2%, however pre-batch testing should always be performed based on the specific concrete types & admixtures used.

PRODUCT SPECIFICATIONS

Parameters (units)	Specifications
Appearance	Pale yellow liquid
Cloud point (°C, BDGE)	40-45
pH (1% aqueous solution)	5.0-7.0
Hydroxyl value (mgKOH/g)	75-82
H ₂ O (%)	≤ 0.5
CHROMA (Pt-Co,50°C)	≤ 100



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia

chemport.com.au

PACKAGING

180kg Drums and 1000kg totes

STORAGE & SHELF LIFE

Product should be stored in a dry place away from direct sunlight in sealed, original packaging.

SAFETY & HANDLING

Please consult the Material Safety Data Sheet for additional information on safety, handling and storage before using this product.