



METHOD™ HPMC 20K S

Hydroxypropyl Methylcellulose Ether

DESCRIPTION

METHOD™ HPMC 20K S is a hydroxypropyl methylcellulose ether designed for use in drymix mortar and construction chemical applications requiring delayed dissolution, water retention, thickening performance, and improved workability. The product is recommended for skim coat, tile adhesive, tile grout, repair mortar, and crack filler formulations where enhanced application properties and bonding performance are required.

KEY FEATURES

- Good workability
- Excellent water retention
- Good thickening performance
- Improved bonding strength
- Good film-forming properties
- Delayed dissolution characteristics
- Suitable for drymix mortar systems

APPLICATIONS

- Skim coat formulations
 - Tile adhesives
 - Tile grouts
 - Repair mortars
 - Crack fillers
 - Drymix mortar systems
 - Construction chemical formulations
-

TYPICAL SPECIFICATIONS

PROPERTY	TYPICAL VALUE
Appearance	White powder
Viscosity	Approx. 15,000 – 25,000 mPa·s
pH	5.0 – 9.0
Particle Size (through 80 mesh)	95%
Moisture Content	Max. 6.0%
Ash Content	Max. 5.0%
Test Condition	2% solution, 20°C, Brookfield, 20 rpm

LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

Supplied in 25 kg paper bags with polyethylene inner liner.

STORAGE & HANDLING

Store in a cool, dry, and clean environment away from direct sunlight and moisture exposure. Keep packaging tightly sealed when not in use to maintain product quality and handling performance. 24 months from production date when stored under recommended storage conditions.

SAFETY

Refer to the Safety Data Sheet (SDS) for detailed safety, handling, and regulatory information.