



SILANOX™ 60E

DESCRIPTION

SILANOX™ 60E is a silane/siloxane composite emulsion designed for waterproofing cement-based systems. The product can be incorporated directly into mortar and concrete formulations or applied as a surface treatment to provide excellent hydrophobic performance and long-term water repellency.

KEY FEATURES

- Low dosage with excellent waterproofing performance
- Low VOC and environmentally friendly
- Excellent hydrophobic effect
- Easy to incorporate into cement-based systems
- Suitable for internal admixture and surface treatment applications

APPLICATIONS

- Concrete and mortar admixtures
 - Surface treatment for concrete substrates
 - Cement fiberboard waterproofing
 - Cement-based building materials
 - Waterproof cementitious systems
-

TYPICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Appearance	Milky white liquid
Active Content, %	50 – 52
pH	6.0 – 9.0
Density (25°C), g/cm ³	0.95 – 1.05



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

Available in 200 L drums and 1000 L IBC totes.

STORAGE & HANDLING

Store in a cool, dry environment between 5–35°C. Keep containers sealed when not in use. Shelf life is 12 months under recommended storage conditions.

SAFETY

Refer to the Safety Data Sheet (SDS) for detailed safety, handling, and regulatory information.