



Glass Fibers – Chopped Strand

12 mm

Chopped strand glass fibers are composed of E-glass (calcium aluminoborosilicate) with low dielectric properties and high thermal stability. These characteristics make them suitable for reinforcing composite materials and for use in fire-resistant applications. Standard length is 12 mm; other lengths (3 mm, 6 mm, 18 mm) are available upon request.

APPLICATIONS

- Reinforcement in gypsum and fiberglass composites
- Papermaking and filtration media
- Adhesives and coatings
- Surfacing veils and specialty composites

TYPICAL SPECIFICATIONS

Parameters	Specification
Filament diameter (μm)	~13
Yarn density (TEX)	150 ± 20
Moisture content (%)	< 0.2

(Values are typical and not intended as guaranteed specifications.)



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia

chemport.com.au

PACKAGING

- 25 kg kraft paper bags on pallets
- Super sacks available upon request

STORAGE

Store in a dry location, away from direct sunlight and humidity. Keep sealed in original packaging.

SAFETY

- Avoid dust generation during handling.
- Use appropriate PPE to prevent eye or skin irritation.
- Refer to the Safety Data Sheet (SDS) for detailed information on safe handling, storage, and disposal.