



Sodium Lignosulfonate Powder

CAS No.: 8061-51-6

Formula:

DESCRIPTION

Sodium Lignosulfonate Powder is a free-flowing brown organic polymer derived from the sulfite pulping of wood. It is a water-soluble anionic surfactant and dispersant with binding and chelating properties. The product functions as a low-range water reducer in concrete and a mid-temperature retarder in oil-well cementing systems. Its versatility and natural polymeric structure make it suitable for a wide range of industrial and agricultural applications.

KEY FEATURES

- Organic, environmentally friendly dispersant and binder
- Effective mid-temperature retarder in oilfield cementing
- Improves workability and reduces water demand in concrete
- Enhances granulation and binding in pellets and briquettes
- Compatible with a variety of cement and admixture systems

APPLICATIONS

- Concrete admixtures (plasticizer, water reducer)
- Oilfield cementing retarder
- Pellet binding and dust suppression
- Agrochemical formulations and fertilizer additives
- Textile and dye dispersant systems

TYPICAL SPECIFICATIONS

Parameter	Specification
Appearance	Brown powder
Solids Content	≥ 94.0%
pH (25 °C)	9.0 – 11.0
Specific Gravity	~0.37 g/cm ³



**LIMITED WARRANTY INFORMATION.
PLEASE READ CAREFULLY.**

Chemport Pty Ltd provides the information contained in this document in good faith based on the best knowledge available at the time of publication. While we believe the information to be accurate and reliable, it is intended for general guidance only and is provided without warranty of any kind, express or implied.

Users are solely responsible for determining the suitability of this product for their specific application and for ensuring compliance with all relevant regulations, industry standards, and intellectual property rights. The product must not be used in violation of any law, statute, or third-party rights.

Chemport Pty Ltd shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of this product or reliance on the information provided in this document. Users should refer to the current Safety Data Sheet (SDS) and perform their own evaluations, including any necessary testing, to confirm the product's suitability for use in their particular conditions.

This document is subject to revision without notice as new data becomes available.

TECHNICAL SUPPORT
+61294103317
info@chemport.com.au

Level 9 Tower A
821 Pacific Highway
Chatswood NSW 2067
Australia
chemport.com.au

PACKAGING

- Available in 25 kg bags and 1,000 kg super sacks.
- Also available as a 40% aqueous solution.

SHELF LIFE

Shelf life is at least 12 months under normal storage conditions.

STORAGE

Store in sealed original packaging in a cool, dry area away from direct sunlight.
Avoid exposure to moisture to maintain free-flowing properties.

SAFETY & HANDLING

Avoid contact with eyes and prolonged skin exposure. Use standard protective equipment such as gloves, goggles, and dust masks during handling. Refer to the Safety Data Sheet (SDS) for full information on safe handling, first aid, and disposal procedures.